







72V/200Ah lead acid battery, zero engine emission and no pollution.



Passed CE quality certification.



The small size can work in a small limited space, and is flexible in operation.



Multi-options for attachments.



Standard configuration with Quick Hitch and Electric Joystick, easier to operate.



Lifting Height - 3053mm



Maintenance-Free Batteries makes later use more convenient and more secure.



Rated Load - 900kg









## EREL1000 ELECTRIC WHEEL LOADER

Hydraulic Oil Tank

Brake Fluid



	AFRICA
Performance:	
Rated Load	900kg
Bucket Rated Capacity	0.26m³
Primary Loading Height	1821mm
Dumping Height(Not Extend Boom)	2147mm
Secondary Loading Height	3620mm
Max. Dump Height	2714mm
Max. Grade Ability	20
Oscillation Angle	8°
Dimensions & Weight:	
Overall dimension (L×W×H)	3822*1270*2380mm
Bucket Width (overall)	1200mm
Wheel Base	960mm
Min. Ground Clearance	210mm
Net Weight	2310kg
Battery:	
Battery Model	3-EVF-200A
Rated Capacity	200Ah
No. Of Batteries	12
Rated Voltage	72V
Working Hours	4h
Transmission System:	
Transmission	Hydraulic System
Motor Type	YQP5.72AF.48P
Voltage	72V
Power	5000W
Displacement	14ml/r
Steering System:	
Type of Steering Hydraulic System	Full Hydraulic Steering
System Pressure	16MPa
Type of Steering Pump	External Gear Pump
Steering Cylinder Bore	Ø65mm
Qty	1pc
Braking System:	
Service Brake	Drum Brake
Brake Drum	240mm
Parking Break	Drum Brake
Turoe:	
Tyres:	29*12.50-15
Type Warking Procesure	
Working Pressure	0.3MPa 4
Qty	4
Oil Capacity:	
Hydraulia Oil Tank	401

40L

0.8L