



SHAFTS SCREENER MB-HDS312



A



B


SPECIFICATIONS



Recommended excavator	ton	7 - 11
Weight	ton	0,72
Load capacity	m³	0.35
Pressure	bar	200 - 250
Back pressure	bar	< 20
Oil flow rate*	l/min	75 - 100
Size A	mm	1235
Size B	mm	985
Size C	mm	880

* The minimum hydraulic flow rate value must be alongside the required operating pressure.

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
 RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration
 RM Mixer kit		Coal reduction Soil Aeration Compost Aeration Glass reduction Drywall reduction
 RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil
 RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

OPTIONAL ACCESSORIES

Shaft holder

24 Month Warranty

APPLICATION AREAS



Road works



Tunnels



Enclosed spaces



Pipelines



Inert material
recycling



Excavations



Urban construction
sites



Foundries



Maintaining landscape
and agricultural areas