




# SHAFTS SCREENER MB-HDS407



A



B

## SPECIFICATIONS

	Recommended excavator	ton	3,5 - 5,5
	Recommended backhoe loader	ton	6 - 9*
	Weight	ton	0,28
	Load capacity	m <sup>3</sup>	0.14
	Pressure	bar	200 - 220
	Back pressure	bar	< 20
	Oil flow rate**	l/min	25 - 35
	Size A	mm	765
	Size B	mm	840
	Size C	mm	760

\* Only compatible with the posterior boom of a Backhoe.

\*\* The minimum hydraulic flow rate value must be alongside the required operating pressure.

## SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
RQ15 Sifting kit	15 mm	Sifting damp/dry soil Soil Aeration
RM Mixer kit		Coal reduction Soil Aeration Compost Aeration Glass reduction Drywall reduction
RQ8 Sifting kit	8 mm	Sifting damp/dry soil Soil Aeration

\* Shafts in closed position.

## OPTIONAL ACCESSORIES

Shaft holder	24 Month Warranty
--------------	-------------------

## APPLICATION AREAS



Road works



Tunnels



Enclosed spaces



Pipelines



Inert material  
recycling



Excavations



Urban construction  
sites



Foundries



Maintaining landscape  
and agricultural areas